

DECLARATION OF PERFORMANCE

NO: GRES 01

DRY- PRESSED CERAMIC TILE, WITH WATER ABSORPTION $E_w \leq 0,5 \%$ FOR INTERNAL AND EXTERNAL WALLS AND FLOORINGS

NUOVA RIWAL CERAMICHE SRL , VIA GHIAROLA NUOVA 101, 41042 FIORANO MOEENESE (MO) ITALIA

SYSTEM 4

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	A1_{FL}/A1	EN 14411:2012
Release of dangerous substance, for:		
_Cadmium	NPD	
_Lead	NPD	
Breaking Strength	>1300 N	
Slipperiness	NPD	
Tactility	NPD	
Bond strenght/adhesion, for:		
Cementitious adhesive, type C2	1N/mm2	
Thermal Shock Resistance	PASS	
Durability for:		
_ Internal Use:	PASS	
_ External Use: freeze-thaw resistance	PASS	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by :

ALBERTO ALBONETTI
(Technical Director)

Fiorano Modenese
25/06/2013


